

Cable **tray** Suspension



Description

Cable suspension system for Pemsaband® sheet tray and other items such as luminaires, air conditioning, signalling, etc. For the suspension of sheet tray with Spiderband® it is fixed through the holes of the sidewall by means of a locking system, without the need for screws. Maximum admissible load of 35 kg. Made of steel, with EZ Protection System and available in lengths of 300, 460 and 500 mm.

Advantages

Optimised design for quick and easy use. Installation savings in both material and labour.

It has a loop on the end for the connection of the steel cable.

Suitable for the support of cable trays or other items with loads not exceeding 35 kg.

CE conformity to directive 2014/35 / EU.

PG protection system (standard EN-ISO 2081), silver colour, suitable for indoor installations. Corrosion resistance class 3.

Applications

Suitable for support by cable suspension of Pemsaband® sheet trays, as well as other items (luminaires, air conditioning, signage, etc.). Recommended for indoor installations.

Solutions



Main technical characteristics

 EZ	 10	 Steel with surface coating	 35	 -50 / 150 °C	 Flame retardant	ETIM EC001003
---	--	--	--	--	---	------------------

Product data

L _{mm}	Ref	kg/u
300	62306230	0.023
460	62306240	0.029
550	62306250	0.031

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic

