
PLASTIC 7035 System

29/03/2024

RLH1250 Halogen Free Conduit





Description

RLH rigid pipe for the protection of electrical cables in building applications. Made of halogen-free thermoplastic material (PC + ABS) with an IP44 protection rating, compression strength of 1250 N and impact resistance of 6 J. Available in grey (RAL 7035), in a wide variety of sizes.

Advantages

Compression resistance grade 4, 1250 N. Suitable for surface installations.

Excellent performance against impact.

Quick assembly via plug-in connection between conduits and fittings.

CE conformity to the 2014/35 directive and the IEC 61386 standard.

High security, halogen free material UNE/EN 60754-2 y UNE/EN 60754-1. Reduced smoke opacity and toxicity in the event of a fire. Flame retardant.

Applications

Suitable for the protection of electrical cables in building, tertiary and industrial applications with high safety requirements. Premises of public attendance.

Solutions

EDIFICACIÓN. TERCIARIO

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

RLH1250 Halogen Free Conduit

Main technical characteristics

Colour Grey RAL 7035 | DN NW16, NW20, NW25, NW32, NW40, NW50, NW63 | Polycarbonate + ABS | Cod IEC 61386 4432 | 1250 N | 6 J

IP44 | -15 / 90 °C | LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA | ETIM EC001174

Product data

DN	Od1	Od2	Ref	kg/u	u
NW16	12.8	16	13005116	0.086	57
NW20	16.6	20	13005120	0.117	57
NW25	21.6	25	13005125	0.149	57
NW32	28	32	13005132	0.226	30
NW40	35.2	40	13005140	0.339	30
NW50	45.2	50	13005150	0.431	15
NW63	58	63	13005163	0.572	15

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."