

TM-PVC 7035 Conduit

1/2



Description

TM-PVC 7035 PVC coated GC protection system steel flexible conduit for the protection of wiring. Flexible corrugated conduit with steel strip, waterproof and self-extinguishing protection (IP65), compression resistance of 1250 N and impact resistance of 6 J. Available in grey (RAL 7035), in a wide variety of sizes.

Advantages

High aesthetic component. RAL 7035 grey same as the other conduits or electrical materials.

No flame propagation.

High degree of tightness with RGM and RGP fittings.

CE conformity to the 2014/35 directive and the IEC 61386 standard.

Made in PVC coated galvanised steel, sealed and self-extinguishing.

Applications

Suitable for the protection of wiring and conductors in building, tertiary sector, machinery and industry with high mechanical requirements, electrical installations in suspended and surface conduits according to REBT.

Solutions



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



COLOUR Grey RAL 7035	DN NW 7, NW 9, NW11, NW13, NW16, NW21, NW29, NW36, NW48	Ⓜ ACERO CON PROT. SUPERFICIAL,PVC	Code IEC 61386 4421
--------------------------------	--	--	---

1250 N	6 J	IP65	-5 / 60 °C	Flame retardant	EC001177
--	---	--	--	---	----------

DN				Ref	kg/u	
NW 7	9.7	12.7	31	11060207	0.096	50
NW 9	11.5	14.7	37	11060209	0.101	50
NW11	15.3	18.3	52	11060211	0.145	50
NW13	17.1	20.3	55	11060213	0.158	50
NW16	19.3	22.5	60	11060216	0.183	50
NW21	23.4	27.8	71	11060221	0.368	25
NW29	30.7	34.7	76	11060229	0.473	25
NW36	39.8	44.8	103	11060236	0.616	25
NW48	52.7	55.7	114	11060248	0.877	20

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Reijband, Pemsaband, Inducanal, Rejtech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."