**RPVC Conduit Accessories** 

19/04/2024 1/2

# **RPVC Coupler**



### Description

PVC coupler in grey colour (RAL 7035) with an IP44 protection index for joining RPVC rigid conduits. Assembly by push fit connection to the conduit. Available in different diameters.

#### **Advantages**

For connection of rigid RPVC conduits.

Protection index EN 60529: IP44.

Quick assembly via plug-in connection between conduits and fittings.

CE conformity to the 2014/35 directive and the IEC 61386 standard.

Made of PVC, not flame retardant.

## **Applications**

Suitable for the joining of rigid PVC conduits in building, tertiary and industrial applications.

## Solutions













RPVC Conduit Accessories 19/04/2024

## **RPVC Coupler**

2/2

### Main technical characteristics

COLOUR Grey RAL 7035

DN NW16, NW20, NW25, NW32, NW40, NW50, NW63

M PVC

**\*** -5 / 60

ETIM EC000937

### **Product data**

DN	L <sub>(mm)</sub>	Ref	kg/u	(Fü
NW16	39	55009016	0.004	19
NW20	47	55009020	0.006	19
NW25	57	55009025	0.009	19
NW32	67	55009032	0.014	10
NW40	71	55009040	0.019	10
NW50	91	55009050	0.029	5
NW63	107	55009063	0.042	5

## **S** Protection System

**cu** - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

## **M** Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

**PU** - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic









