

CLH Coupler

1/2



Description

Grey polypropylene coupler (RAL 7035) with an IP44 protection rating for CLH flexible conduits. Accessory for mounting flexible conduits to junction boxes.

Advantages

Supplied complete with nut.

Protection index EN 60529: IP44.

For connection of CLH corrugated conduits to boxes.

CE conformity to the 2014/35 directive and the IEC 61386 standard.

Made from polypropylene, halogen free.

Applications

Suitable for halogen-free corrugated conduits in building, tertiary and industrial applications with high safety requirements. Premises of public attendance.

Solutions



www.pemsa-rejiband.com



Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

Main technical characteristics							
Colour	Grey RAL 7035	DN	NW16, NW20, NW25	⚙️	M16, M20, M25	📦	50
				🔄	Polypropylene	🛡️	IP44
				🔥	-15 / 90 °C		
🚫	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA			ETIM	EC000937		

Product data			
DN	⚙️	Ref	kg/u
NW16	M16	55007116	0.005
NW20	M20	55007120	0.007
NW25	M25	55007125	0.012

🔒 Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass

🏠 Insulating materials
PC+ABS - Halogen Free Polycarbonate + ABS
PVC - Polyvinyl Chloride
PP - Halogen Free Polypropylene
PA6 - Halogen Free Polyamide 6
PA12 - Halogen Free Polyamide 12
PU - Polyurethane
PE - Polyethylene
NBR - NBR rubber
PET - Thermoplastic Polyester
TPV - Thermoplastic