


RB-PA Flexible Conduit



Description

Very flexible corrugated conduit made of self-extinguishing polyamide 12 in grey RAL 7031 or black RAL 9005, halogen-free and with an IP67 protection rating. The RB-PA flexible conduit of the Pemsaflex® range is recommended for industrial applications, machinery and where high mechanical characteristics are required with a high degree of flexibility.

Advantages

Manufactured in polyamide 12. Self-extinguishing, halogen-free and flame-retardant.

Excellent performance and flexibility in long work cycles.

Working temperature: -450C to + 105°C.

Protection index EN 60529: IP67 with the suitable fittings.

UL and CSA certification. BD approval. CE conformance with the 2014/35 directive and the IEC 61386 standard. Halogen-free according to EN 50267-2-1 standard. In accordance with standard EN 60204-1 (machine safety).

Applications

It is recommended for use in industrial applications and electrical installations of machine tools, robot equipment and vehicles. Excellent flexibility and behaviour in outdoor applications.

Solutions



Main technical characteristics							
Colour Grey RAL 7011, Black RAL 9005		DN NW 7, NW10, NW12, NW17, NW23, NW29, NW36, NW48, NW52, NW70			Poyamide 12		1342
125 N	2 J	IP67	-25 / 90 °C	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA		Resistant	ETIM EC001175

Product data							
COLOUR	DN	Øi	Øe	Le	Ref	kg/u	Reel
Grey RAL 7011	NW 7	6.4	10	15	10046007	0.023	100
Grey RAL 7011	NW10	9.6	13	20	10046010	0.027	100
Grey RAL 7011	NW12	11.8	15.7	25	10046012	0.036	50
Grey RAL 7011	NW17	16.7	21.7	30	10046017	0.057	50
Grey RAL 7011	NW23	21.8	28.3	35	10046023	0.094	50
Grey RAL 7011	NW29	28.1	34.1	40	10046029	0.122	50
Grey RAL 7011	NW36	35.5	42.3	60	10046036	0.164	30
Grey RAL 7011	NW48	46.5	54.5	70	10046048	0.224	30
Grey RAL 7011	NW52	52.4	62.5	125	10046052	0.365	30
Grey RAL 7011	NW70	69.3	82.5	150	10046070	0.460	30
Black RAL 9005	NW 7	6.4	10	15	10047007	0.023	100
Black RAL 9005	NW10	9.6	13	20	10047010	0.027	100
Black RAL 9005	NW12	11.8	15.7	25	10047012	0.036	50
Black RAL 9005	NW17	16.7	21.7	30	10047017	0.057	50
Black RAL 9005	NW23	21.8	28.3	35	10047023	0.094	50
Black RAL 9005	NW29	28.1	34.1	50	10047029	0.122	50
Black RAL 9005	NW36	35.5	42.3	60	10047036	0.164	30
Black RAL 9005	NW48	46.5	54.5	70	10047048	0.224	30
Black RAL 9005	NW52	52.4	62.5	125	10047052	0.365	30
Black RAL 9005	NW70	69.3	82.5	150	10047070	0.460	10

Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass

Insulating materials
PC+ABS - Halogen Free Polycarbonate + ABS

RB-PA Flexible Conduit

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

