

### Description

Conduit end support of self-extinguishing, halogen-free polyamide 12 available in various sizes. It is used in conjunction with clamps and has tabs for the correct fastening of RB-PA and RB-PU conduits in Robotics applications.

### Advantages

Manufactured in polyamide 12. Self-extinguishing, halogen-free and flame-retardant.

Fixing the end of the tube together with clamps in robot joints.

Working temperature: -25°C to + 90°C.

It has tabs for the correct attachment of RB-PA and RB-PU flexible conduits.

CE conformity to the 2014/35 directive and the IEC 61386 standard.

### Applications

Suitable for Robotics and wiring installations for robot arms in assembly lines, industrial applications, etc.





### Solutions



Main technical characteristics

ETIM  
EC000127

Product data

COLOUR	DN	REF	kg/u				
Black RAL 9005	NW70	33110170	0.039	10	Poyamide 12	-25 °C	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA

Protection System

- CU** - Copper electroplated
- PG** - Pregalvanised
- EZ** - Electrogalvanised
- BC** - Electrogalvanised Bichromate
- BK8** - High Resistance Coating
- GC** - Hot Dip Galvanising
- INOX** - Stainless Steel
- PT** - Polyester Paint
- AL** - Aluminum
- LN** - Brass or Nickel-plated brass

Insulating materials

- PC+ABS** - Halogen Free Polycarbonate + ABS
- PVC** - Polyvinyl Chloride
- PP** - Halogen Free Polypropylene
- PA6** - Halogen Free Polyamide 6
- PA12** - Halogen Free Polyamide 12
- PU** - Polyurethane
- PE** - Polyethylene
- NBR** - NBR rubber
- PET** - Thermoplastic Polyester
- TPV** - Thermoplastic

