
MACROFLEX Accessories 25/04/2024

### Fibre Washer I

1/2











# Description

Type I fibre washer in black nitrile RAL 9005 with an IP65 degree of protection available in NW70 and NW95 diameters for mounting in the surface of the fixing ring of the Macroflex® range of fittings.

#### **Advantages**

Mounting inside fittings of the Macroflex® range.

Protection index EN 60529: IP65.

Working temperature: -25°C to + 105°C.

Manufactured in NBR elastomer.

CE conformity to the 2014/35 directive and the IEC 61386 standard.

#### **Applications**

Suitable for fixing large diameter Pemsaflex® and Macroflex® conduits for the protection of wiring and conductors in electrical installations of machines, tools, industrial equipment, robots, vehicles and special installations.

## Solutions











MACROFLEX Accessories 25/04/2024

#### Fibre Washer I

2/2

## Main technical characteristics

CoLOUR Black RAL 9005

ETIM EC000098 DN NW70, NW95

kg/u 0.001 ₩ 10 M NBR

**\*** -25 / 90

Flame retardant

°C

**Product data** 

DN	Rer
NW70	33090070
NW95	33090095

# **S** Protection System

CU - Copper electroplated

**PG** - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

# **M** Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

**PP** - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

