
19/04/2024 MACROFLEX Accessories

Fibre Washer II











1/2



Description

Type II fibre washer in black nitrile RAL 9005 with an IP65 degree of protection available in NW70 and NW95 diameters for mounting on the connection of the fitting to the conduit in the Macroflex® range.

Advantages

Mounting inside fittings of the Macroflex® range.

Protection index EN 60529: IP65.

Working temperature: -25°C to + 105°C.

Manufactured in NBR elastomer.

CE conformity to the 2014/35 directive and the IEC 61386 standard.

Applications

Suitable for fixing large diameter Pemsaflex® and Macroflex® conduits for the protection of wiring and conductors in electrical installations of machines, tools, industrial equipment, robots, vehicles and special installations.

Solutions













MACROFLEX Accessories 19/04/2024

Fibre Washer II

2/2

Main technical characteristics

CoLOUR Black RAL 9005

ETIM EC000098 DN NW70, NW95

kg/u 0.001 ₩ 10 M NBR

***** -25 / 90

Flame retardant

°C

Product data

DN	Ref
NW70	33090170
NW95	33090195

S Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

M Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic











