



Description

Zinc plated steel clamp with elastomer profile for fixing Macroflex® NW70 and NW95 conduits that protects it from vibrations.

Advantages

Manufactured in PG protection system steel with a NBR elastomer profile.

Available in various sizes.

Working temperature: -25°C to + 90°C.

Protect from vibrations.

CE conformity to the 2014/35 directive and the IEC 61386 standard.

Applications

Suitable for fixing large diameter Pemsaflex® and Macroflex® conduits for the protection of wiring and conductors in electrical installations of machines, tools, industrial equipment, robots, vehicles and special installations.

Solutions



Main technical characteristics

Ⓢ EZ	Ⓢ EZ2, Electrogalvanised	DN NW70, NW95	A _(mm) 25	10	Ⓜ ACERO CON PROT. SUPERFICIAL,NBR
🔥 -15 / 120 °C	🚫 LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA			ETIM EC000464	

Product data

DN	L _(mm)	C _(mm)	H _(mm)	Ref	kg/u
NW70	131	8.2	112	33090270	0.059
NW95	150	8.3	132	33090295	0.075

Ⓢ Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Ⓜ Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic

