


## PA Braided Tubing



### Description

Elasticated monofilament sheath, halogen-free, for cable management. Available in different diameters. Made of self-extinguishing polyamide 6, grey RAL 7035 and black RAL 9005.

### Advantages

Manufactured in polyamide 6. Self-extinguishing, halogen-free according to UNE/EN 60754-2 y UNE/EN 60754-1 and flame-retardant.

Halogen free.

Available in colours: grey RAL 7035 and black RAL 9005.

CE conformity to the 2014/35 directive and the IEC 61386 standard.

### Applications

Suitable for the protection and management of wiring for general and industrial applications.

### Solutions



### Main technical characteristics

**COLOUR** Grey RAL 7031, Black RAL 9005

DN NW 4, NW 6, NW 8, NW10, NW12, NW16, NW20, NW25, NW30, NW40, NW50, NW60

 Poyamide 6

 LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA

ETIM  
EC002254

## Product data

| COLOUR         | DN   |  | A <sub>mm</sub> | B <sub>mm</sub> | REF      | kg/u  |  |  |
|----------------|------|-----------------------------------------------------------------------------------|-----------------|-----------------|----------|-------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Grey RAL 7031  | NW 4 | 3 / 6                                                                             | 3               | 6               | 12000004 | 0.004 | 100                                                                                 | -25 / 150 °C                                                                        |
| Grey RAL 7031  | NW 6 | 5 / 8                                                                             | 5               | 8               | 12000006 | 0.005 | 100                                                                                 | -25 / 150 °C                                                                        |
| Grey RAL 7031  | NW 8 | 7 / 11                                                                            | 7               | 11              | 12000008 | 0.006 | 100                                                                                 | -25 / 150 °C                                                                        |
| Grey RAL 7031  | NW10 | 7 / 15                                                                            | 7               | 15              | 12000010 | 0.009 | 100                                                                                 | -25 / 150 °C                                                                        |
| Grey RAL 7031  | NW12 | 8 / 18                                                                            | 8               | 18              | 12000012 | 0.014 | 100                                                                                 | -25 / 150 °C                                                                        |
| Grey RAL 7031  | NW16 | 15 / 21                                                                           | 15              | 21              | 12000016 | 0.015 | 100                                                                                 | -25 / 150 °C                                                                        |
| Grey RAL 7031  | NW20 | 18 / 30                                                                           | 18              | 30              | 12000020 | 0.022 | 100                                                                                 | -25 / 150 °C                                                                        |
| Grey RAL 7031  | NW25 | 24 / 36                                                                           | 24              | 36              | 12000025 | 0.024 | 100                                                                                 | -25 / 150 °C                                                                        |
| Grey RAL 7031  | NW30 | 32 / 47                                                                           | 32              | 47              | 12000030 | 0.034 | 50                                                                                  | -25 / 150 °C                                                                        |
| Grey RAL 7031  | NW40 | 35 / 58                                                                           | 32              | 58              | 12000040 | 0.042 | 50                                                                                  | -25 / 150 °C                                                                        |
| Grey RAL 7031  | NW50 | 32 / 68                                                                           | 32              | 68              | 12000050 | 0.051 | 50                                                                                  | -25 / 150 °C                                                                        |
| Grey RAL 7031  | NW60 | 32 / 85                                                                           | 32              | 85              | 12000060 | 0.069 | 50                                                                                  | -25 / 60 °C                                                                         |
| Black RAL 9005 | NW 4 | 3 / 6                                                                             | 3               | 6               | 12000104 | 0.004 | 100                                                                                 | -25 / 150 °C                                                                        |
| Black RAL 9005 | NW 6 | 5 / 8                                                                             | 5               | 8               | 12000106 | 0.005 | 100                                                                                 | -25 / 150 °C                                                                        |
| Black RAL 9005 | NW 8 | 7 / 11                                                                            | 7               | 11              | 12000108 | 0.006 | 100                                                                                 | -25 / 150 °C                                                                        |
| Black RAL 9005 | NW10 | 7 / 15                                                                            | 7               | 15              | 12000110 | 0.009 | 100                                                                                 | -25 / 150 °C                                                                        |
| Black RAL 9005 | NW12 | 8 / 18                                                                            | 8               | 18              | 12000112 | 0.014 | 100                                                                                 | -25 / 150 °C                                                                        |
| Black RAL 9005 | NW16 | 15 / 21                                                                           | 15              | 21              | 12000116 | 0.015 | 100                                                                                 | -25 / 150 °C                                                                        |
| Black RAL 9005 | NW20 | 18 / 30                                                                           | 18              | 30              | 12000120 | 0.022 | 100                                                                                 | -25 / 150 °C                                                                        |
| Black RAL 9005 | NW25 | 24 / 36                                                                           | 24              | 36              | 12000125 | 0.024 | 100                                                                                 | -25 / 150 °C                                                                        |
| Black RAL 9005 | NW30 | 32 / 47                                                                           | 32              | 47              | 12000130 | 0.034 | 50                                                                                  | -25 / 150 °C                                                                        |
| Black RAL 9005 | NW40 | 32 / 58                                                                           | 32              | 58              | 12000140 | 0.042 | 50                                                                                  | -25 / 150 °C                                                                        |
| Black RAL 9005 | NW50 | 32 / 68                                                                           | 32              | 68              | 12000150 | 0.051 | 50                                                                                  | -25 / 150 °C                                                                        |
| Black RAL 9005 | NW60 | 32 / 85                                                                           | 32              | 85              | 12000160 | 0.069 | 50                                                                                  | -25 °C                                                                              |

**Protection System**

**CU** - Copper electroplated

**PG** - Pregalvanised

**EZ** - Electrogalvanised

**BC - Electrogalvanised Bichromate**

### BK8 - High Resistance Coating

**GC** - Hot Dip Galvanising

**INOX** - Stainless Steel

**PT** - Polyester Paint

**AL** - Aluminum



[www.pemsa-rejiband.com](http://www.pemsa-rejiband.com)

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Reijband, Pemsaband, Inducanal, Reijtech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



PA Braided Tubing

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

