Supports Technical Floors 17/04/2024

Stand off Bracket







Description

Metal support that allows vertical or horizontal wall and floor mounting of Rejiband® and Pemsaband® trays. Attaches to the tray by using the Rejiband® Fastening. Made of steel and available in various sizes and Protection Systems.

Advantages

Can be used in both wall and floor installations.

Allows the installation of the tray at a distance of 40 mm from the wall or floor.

Due to its U-shape, it allows for uneven surfaces of the wall or floor.

Applications

It is suitable for the installation of Rejiband® and Pemsaband® trays and can be mounted vertically on a wall and is an efficient and simple solution as well in false floor installations.

Solutions





INDUSTRIA ALIMENTARIA FOTOVOLTAICA















Supports Technical Floors 17/04/2024

Stand off Bracket

2/2

Main technical characteristics

180, 350

₩ 10

^{CTA} 100

🐮 -50 / 150 °C

A1 No combustible

EC000022

Product data

S	Cless IEC 615.37		Ref	kg/u	⊚
PG	Class 3	180	67030539	0.217	Steel with surface coating
PG	Class 3	350	67030540	0.337	Steel with surface coating
GC	Class 6	180	67030541	0.224	Steel with surface coating
GC	Class 6	350	67030542	0.348	Steel with surface coating
INOX	Class 9D	180	67060541	0.145	Acero inoxidable AISI 316L
INOX	Class 9D	350	67060542	0.225	Acero inoxidable AISI 316L

S Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

M Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

PET - Thermoplastic Polyester

TPV - Thermoplastic











