


Protective cap



Description

Advantages

Applications

Solutions



Main technical characteristics

Colour	Black RAL 9005, Red RAL 3000	 Poyamide 6	 -20 / 100 °C	 LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA	ETIM
--------	------------------------------	--	--	--	------

Product data

COLOUR	Ø	Ref	kg/u	kg
Black RAL 9005	3 / 6.5	44040007	0.000	1000
Black RAL 9005	4 / 8	44040009	0.001	1000
Black RAL 9005	5 / 10	44040011	0.001	1000
Black RAL 9005	6 / 12	44040013	0.001	500
Black RAL 9005	10 / 14	44040016	0.002	500
Black RAL 9005	13 / 18	44040021	0.002	500
Black RAL 9005	18 / 25	44040029	0.005	200
Black RAL 9005	22 / 32	44040036	0.009	100
Black RAL 9005	32 / 38	44040042	0.011	50
Black RAL 9005	37 / 44	44040048	0.014	50
Red RAL 3000	3 / 6.5	44041007	0.000	1000
Red RAL 3000	4 / 8	44041009	0.001	1000
Red RAL 3000	5 / 10	44041011	0.001	1000
Red RAL 3000	6 / 12	44041013	0.001	500
Red RAL 3000	10 / 14	44041016	0.002	500
Red RAL 3000	13 / 18	44041021	0.002	500
Red RAL 3000	18 / 25	44041029	0.005	200
Red RAL 3000	22 / 32	44041036	0.009	100
Red RAL 3000	32 / 38	44041042	0.011	50
Red RAL 3000	37 / 44	44041048	0.014	50

 Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

 Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride

Caps

19/04/2024

Protective cap

3/3

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

