

# Variable Clip






## Description

Halogen-free polyamide 6 pressure clip in grey color (RAL 7035) for rigid and flexible halogen free and PVC conduits. Accessory for the assembly of the tube by means of a safety lock. Available in different sizes.

## Advantages

It has a lateral connection system with another clip that allows for the parallel assembly of the conduits.

Fastening system with safety lock adaptable to various diameters of conduit.

Suitable for the fixing of rigid and corrugated conduits.

CE conformity to the 2014/35 directive and the EN IEC 61386 standard.

Manufactured in polyamide 6. Self-extinguishing, halogen-free according to UNE/EN 60754-2 y UNE/EN 60754-1 and flame-retardant.

## Applications

Suitable for fixing RLH, CLH, RPVC and CPVC rigid and corrugated conduits for the protection of electric cables in building, tertiary and industrial applications.

## Solutions



Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

# Variable Clip

## Main technical characteristics

| | | | | |
|---|---|---|---|---|
| Colour Grey RAL 7035 | Polyamide 6 | -15 / 90 °C | LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA | ETIM 10 EC002320 |

## Product data

| Ø | Ref | kg/u | |
|---|---|---|---|
| 12 / 20 | 55024012 | 0,006 | 50 |
| 20 / 32 | 55024020 | 0,010 | 40 |
| 32 / 50 | 55024032 | 0,016 | 20 |

## Protection System

**CU** - Copper electroplated

**PG** - Pregalvanised

**EZ** - Electrogalvanised

**BC** - Electrogalvanised Bichromate

**BK8** - High Resistance Coating

**GC** - Hot Dip Galvanising

**INOX** - Stainless Steel

**PT** - Polyester Paint

**AL** - Aluminum

**LN** - Brass or Nickel-plated brass

## Insulating materials

**PC+ABS** - Halogen Free Polycarbonate + ABS

**PVC** - Polyvinyl Chloride

**PP** - Halogen Free Polypropylene

**PA6** - Halogen Free Polyamide 6

**PA12** - Halogen Free Polyamide 12

**PU** - Polyurethane

**PE** - Polyethylene

**NBR** - NBR rubber

**PET** - Thermoplastic Polyester

**TPV** - Thermoplastic



Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."