



Description

Halogen-free polyamide 6 pressure clip in grey color (RAL 7035) for rigid and flexible halogen free and PVC conduits. Accessory for the assembly of the tube by means of a safety lock. Available in different sizes.

Advantages

Suitable for the fixing of rigid and corrugated conduits.

CE conformity to the 2014/35 directive and the IEC 61386 standard.

It has a lateral connection system with another clip that allows for the parallel assembly of the conduits.

Manufactured in polyamide 6. Self-extinguishing, halogen-free according to UNE/EN 60754-2 y UNE/EN 60754-1 and flame-retardant.

Fastening system with safety lock adaptable to various diameters of conduit.

Applications

Suitable for fixing RLH, CLH, RPVC and CPVC rigid and corrugated conduits for the protection of electric cables in building, tertiary and industrial applications.

Solutions



Product data			
Colour		Grey RAL 7035	
Cable diameter range		32 / 50	
kg/u		0.016	
u		20	
Material		Poyamide 6	
Working temperature range (°C)		-15 / 90 °C	
Fire resistance		LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA	

Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass

Insulating materials
PC+ABS - Halogen Free Polycarbonate + ABS
PVC - Polyvinyl Chloride
PP - Halogen Free Polypropylene
PA6 - Halogen Free Polyamide 6
PA12 - Halogen Free Polyamide 12
PU - Polyurethane
PE - Polyethylene
NBR - NBR rubber
PET - Thermoplastic Polyester
TPV - Thermoplastic