



Description

Articulated riser dropper for creating level changes, with adjustable angles, for Megaband® REP ladder. Of 70 mm height. Fixing using M8 hexagonal bolts and nuts. Made from steel with GC Protection system.

Advantages

Conforms to IEC 61537 and CE Conformity to Directive 2014/35/EU.

Thanks to the articulation it allows the creation of level changes.

GC Protection System, Class 8 according to IEC 61537.

Requires M8 hexagonal bolts and nuts.

Applications

Suitable for creating adjustable angle level changes in Megaband® REP ladder in electrical and telecommunications installations and supporting heavy loads in industrial, petrochemical, oil & gas, power plants, mining and cement installations.

Solutions



Product data			
ETIM 10		EC002413	
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		1,432	
Protection System		GC	
Finish		HDG, Hot Dip Galvanised	
Resistance Class		Class 7	
Flange (mm)		70	
kg/u		0,553	
u		2	
Material		Steel with surface coating	
Working temperature range (°C)		-50 / 150 °C	
Fire resistance		A1 No combustible	

Ⓢ Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass

Ⓜ Insulating materials
PC+ABS - Halogen Free Polycarbonate + ABS
PVC - Polyvinyl Chloride
PP - Halogen Free Polypropylene
PA6 - Halogen Free Polyamide 6
PA12 - Halogen Free Polyamide 12
PU - Polyurethane
PE - Polyethylene
NBR - NBR rubber
PET - Thermoplastic Polyester
TPV - Thermoplastic