



Description

Articulated riser dropper for creating level changes, with adjustable angles, for Megaband® REP ladder. Of 100 mm height. Fixing using M8 hexagonal bolts and nuts. Made from steel with GC Protection system.

Advantages

Conforms to IEC 61537 and CE Conformity to Directive 2014/35/EU.

Thanks to the articulation it allows the creation of level changes.

GC Protection System, Class 8 according to IEC 61537.

Requires M8 hexagonal bolts and nuts.

Applications

Suitable for creating adjustable angle level changes in Megaband® REP ladder in electrical and telecommunications installations and supporting heavy loads in industrial, petrochemical, oil & gas, power plants, mining and cement installations.

Solutions



Product data

ETIM 10	EC002413	u	2
Huella de CO2. GWP A1-A3 (kg CO2 eq.)	2,015	Material	Steel with surface coating
Protection System	GC	Working temperature range (°C)	-50 / 150 °C
Finish	HDG, Hot Dip Galvanised	Fire resistance	A1 No combustible
Resistance Class	Class 7		
Flange (mm)	100		
kg/u	0,778		

🔩 Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

🔧 Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic