



Description

Spiderband® block self-locking for the cable suspension of Rejiband® wire mesh trays, Pemsaband® sheet trays and other items such as luminaires, pipes, air conditioning, signalling etc. With AL protection system. It is the main item in the kit of parts of the Spiderband® system acting by locking the steel cable in an easy and quick way. Available for a maximum load of 10, 50 and 120 kg. Made of aluminium.

Advantages

UL certification, LLOYDS BRITISH and TUV.

Optimised design for quick and easy use. Installation savings in both material and labour.

Is available in three versions depending on the type of wire rope and the maximum permissible load, 10, 50 or 120 kg.

Key element for multiple suspension options by steel cable with the Spiderband® System.

Made of high performance aluminum, which ensures correct operation.

Applications

Suitable for Spiderband® cable suspension installations, for Rejiband® wire mesh trays, Pemsaband® sheet trays and other items such as luminaires, pipes, air conditioning, signage, etc. Recommended for indoor installations.

Solutions



Product data

Protection System	AL	Material	Aluminum
Finish	ALU, Aluminium	SWL (kg)	120
kg/u	0.052	Working temperature range (°C)	-50 / 150 °C
u	10		

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic

