pemsa

Spiderband. Wire Rope Suspension System

Vertical Block





Description

Vertical block kit for Spiderband® cable suspension system. It consists of a 1 m length cable with a tilting anchor on one end, which allows the connection to the horizontal block cable, and a self locking block that allows connection to any tray or other item that requires supporting. Maximum load of 35 kg. Made of steel and with EZ Protection System.

Advantages

Optimised design for quick and easy use. Installation savings in both material and labour.

Versatile system of support. It is used in conjunction with the horizontal Block Kit to create intermediate points for supports with large spans.

Maximum point load 35 kg.

CE conformity to directive 2014/35 / EU.

PG protection system (standard EN-ISO 2081), silver colour, suitable for indoor installations. Corrosion resistance class 3.

Applications

Suitable for creating a vertical fixing or anchoring point, in horizontal catenary structures, together with the Horizontal Block Kit or other systems for cable suspension of Rejiband® wire mesh trays, Pemsaband® sheet trays and other items such as luminaires, pipes, air conditioning, signalling, etc. Recommended for indoor installations.

Solutions



🖽 MARE-1 😫 🛯 😁 🖪 (E 🗰 E90

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

pemsa

Spiderband. Wire Rope Suspension System

Vertical Block

19/04/2024 <mark>2/2</mark>

Main technical characteristics

ETIM EC001003

Product data

| S | (J) | Ref | kg/u | ¢. | 0 | ∫CTA (₀g)↓ | ₩. |
|----|-----|----------|-------|----|----------------------------|---------------|--------------|
| EZ | 1 | 62310201 | 0.075 | 10 | Steel with surface coating | 35 | -50 / 150 °C |

| © Protection System | | | | | |
|---|--|--|--|--|--|
| CU - Copper electroplated | | | | | |
| PG - Pregalvanised | | | | | |
| EZ - Electrogalvanised | | | | | |
| BC - Electrogalvanised Bichromate | | | | | |
| BK8 - High Resistance Coating | | | | | |
| GC - Hot Dip Galvanising | | | | | |
| INOX - Stainless Steel | | | | | |
| PT - Polyester Paint | | | | | |
| AL - Aluminum | | | | | |
| LN - Brass or Nickel-plated brass | | | | | |
| Insulating materials | | | | | |
| PC+ABS - Halogen Free Polycarbonate + ABS | | | | | |
| PVC - Polyvinyl Chloride | | | | | |
| PP - Halogen Free Polypropylene | | | | | |
| PA6 - Halogen Free Polyamide 6 | | | | | |
| PA12 - Halogen Free Polyamide 12 | | | | | |
| PU - Polyurethane | | | | | |
| PE - Polyethylene | | | | | |
| NBR - NBR rubber | | | | | |

PET - Thermoplastic Polyester

TPV - Thermoplastic



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."