CLH Coupler



Description

Grey polypropylene coupler (RAL 7035) with an IP44 protection rating for CLH flexible conduits. Accessory for mounting flexible conduits to junction boxes.

Advantages

Supplied complete with nut.

Protection index EN 60529: IP44.

For connection of CLH corrugated conduits to boxes.

CE conformity to the 2014/35 directive and the EN IEC 61386 standard.

Made from polypropylene, halogen free.

Applications

Suitable for halogen-free corrugated conduitss in building, tertiary and industrial applications with high safety requirements. Premises of public attendance.

Solutions

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

CLH Coupler

Main technical characteristics

Colour Grey RAL 7035	DN NW16, NW20, NW25	M16, M20, M25	50	Polypropylene	IP44	-15 / 90 °C

LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA

ETIM 10 EC000939

Product data

DN		Ref	kg/u
NW16	M16	55007116	0,005
NW20	M20	55007120	0,007
NW25	M25	55007125	0,012

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."