



Description

Grey polypropylene coupler (RAL 7035) with an IP44 protection rating for CLH flexible conduits. Accessory for mounting flexible conduits to junction boxes.

Advantages

CE conformity to the 2014/35 directive and the EN IEC 61386 standard.

Made from polypropylene, halogen free.

Protection index EN 60529: IP44.

For connection of CLH corrugated conduits to boxes.

Supplied complete with nut.

Applications

Suitable for halogen-free corrugated conduits in building, tertiary and industrial applications with high safety requirements. Premises of public attendance.

Solutions



Product data

ETIM 10	EC000939	Material	Polypropylene
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		IP	IP44
Colour	Grey RAL 7035	Working temperature range (°C)	-15 / 90 °C
DN	NW20	Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA
M/PG	M20		
kg/u	0,007		
u	50		

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

