


Articulates Riser Section MEGA**band** (Ref: 93435100)

1/6



Description

Articulated metal accessory consisting of a straight section with two welded crosspieces, with safety edge for the creation of a level change in the Megaband® ladder. Of 120 mm height, Width 100 mm, With GC protection system, HDG finish. It allows to make rises, drops and changes of height in variable angles of 15, 30, 45 and 90°. Quick connection assembly using the click system, without joints. Made of steel in various sizes and Protection Systems.

Advantages

Curved safety edge which offers maximum protection.

Available in various protection systems: GC and stainless steel AISI304 and AISI316L.

The angle is variable by 15°, 30°, 45° and 90°. Sections can be coupled together to provide a greater radius for large cables.

Electrical continuity guaranteed according to standard IEC61537.

Use in conjunction with Megaband® articulated riser plates and Megaband® M8 joint kit or M8 nuts and bolts.

Applications

Suitable for level changes in cable management in Megaband® ladders in electrical and telecommunications installations in public buildings, infrastructures and civil works, industrial facilities, tertiary sector.

Solutions



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



Articulates Riser Section MEGA**band** (Ref: 93435100)

Product data			
ETIM 10		EC001535	
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		5,752	
Protection System		GC	
Finish		HDG, Hot Dip Galvanised	
Resistance Class		Class 6	
Flange (mm)		120	
Width (mm)		100	
kg/u		2,221	
u		1	
Material		Steel with surface coating	
Impact Strength (J)		20 J	
Working temperature range (°C)		-50 / 150 °C	
Fire resistance		A1 No combustible	


Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass

Insulating materials
PC+ABS - Halogen Free Polycarbonate + ABS
PVC - Polyvinyl Chloride
PP - Halogen Free Polypropylene
PA6 - Halogen Free Polyamide 6
PA12 - Halogen Free Polyamide 12
PU - Polyurethane
PE - Polyethylene
NBR - NBR rubber
PET - Thermoplastic Polyester
TPV - Thermoplastic



Articulates Riser Section MEGAband (Ref: 93435100)


Product applications




Articulates Riser Section MEGAband (Ref:

4/6

93435100)



Articulates Riser Section MEGAband (Ref: 93435100)



Articulates Riser Section MEGAband (Ref: 93435100)

