


Articulates Riser Section MEGAband (Ref: 93435600)

1/6



Description

Articulated metal accessory consisting of a straight section with two welded crosspieces, with safety edge for the creation of a level change in the Megaband® ladder. Of 120 mm height, Width 600 mm, With GC protection system, HDG finish. It allows to make rises, drops and changes of height in variable angles of 15, 30, 45 and 90°. Quick connection assembly using the click system, without joints. Made of steel in various sizes and Protection Systems.

Advantages

Curved safety edge which offers maximum protection.

Available in various protection systems: GC and stainless steel AISI304 and AISI316L.

The angle is variable by 15°, 30°, 45° and 90°. Sections can be coupled together to provide a greater radius for large cables.

Electrical continuity guaranteed according to standard IEC61537.

Use in conjunction with Megaband® articulated riser plates and Megaband® M8 joint kit or M8 nuts and bolts.

Applications

Suitable for level changes in cable management in Megaband® ladders in electrical and telecommunications installations in public buildings, infrastructures and civil works, industrial facilities, tertiary sector.

Solutions



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



Product data			
ETIM 10		EC001535	
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		8,057	
Protection System		GC	
Finish		HDG, Hot Dip Galvanised	
Resistance Class		Class 6	
Flange (mm)		120	
Width (mm)		600	
kg/u		3,111	
u		1	
Material		Steel with surface coating	
Impact Strength (J)		20 J	
Working temperature range (°C)		-50 / 150 °C	
Fire resistance		A1 No combustible	

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene


NBR - NBR rubber

PET - Thermoplastic Polyester


TPV - Thermoplastic

Articulates Riser Section MEGAband (Ref: 93435600)


Product applications



Articulates Riser Section MEGAband (Ref: 93435600)



Articulates Riser Section MEGAband (Ref: 93435600)



Articulates Riser Section MEGAband (Ref: 93435600)

