Megaband CPS Accessories

17/11/2026

Megaband CPS 30° Inside Riser



Description

Metal accessory for creating a 30° inside riser in the wiring installation with the Megaband® CPS ladder. It allows descents and height changes to be made with great ease. Radius of curve 200 and 600. Made from Aluminium alloy 6063T6.

Advantages

Its design allows to make drops and changes of angle at 30° with great ease

Available in 100 mm height and 200, 300, 400 and 600 mm wide.

Only the Megaband® M8 joint kit or M8 nuts and bolts required

Conforms to IEC 61537 and CE Conformity to Directive 2014/35/EU.

Made of Aluminum alloy 6063T6. Excellent corrosion resistance.

CEPSA product approval according to ESP-2208-5 specification.

Applications

Suitable for cable conduit installations in the Oil & Gas and Petrochemical Industry, Offshore Platforms, Ports and Maritime Applications in general. Industrial projects in aggressive environments and with high corrosion on the coast and seashore, Power Plants and Renewable Energy.

Solutions

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

Megaband CPS 30° Inside Riser

Main technical characteristics

AL	100	200, 300, 400, 600	800	30	1	Aluminum	20 J	-50 / 150 °C

A1 No combustible	ETIM 10 EC001535

Product data

	REF	kg/u
200	82002299	4,050
300	82002300	4,320
400	82002301	4,580
600	82002302	5,110

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."