


**90° Inside Riser MEGAband** ( Ref: 93515150 )



### Description

Metal accessory for the creation of an inside riser in the wiring installation with the Megaband® ladder. Of 120 mm height, Width 150 mm, With PG protection system, PG3 finish. It allows to make rises and changes of angle at 90° with great ease. Quick connection assembly using the click system. Made of steel, in various sizes and Protection Systems. Bending radius 300 mm. Check availability of 600 mm radius.

### Advantages

Curved safety edge which offers maximum protection.

Connection to ladder by rapid assembly Click system. Only the Megaband® M8 joint kit or M8 nuts and bolts required

Available in various protection systems: EZ, GC and stainless steel AISI 304 and AISI 316L.

Electrical continuity guaranteed according to standard IEC61537.

Its design allows to make rises and changes of height with ease.

### Applications

Suitable for level changes in cable management in Megaband® trays in electrical and telecommunications installations in public buildings, infrastructures and civil works, industrial facilities, tertiary sector. Designed to withstand very high loads.

### Solutions



[www.pemsa-rejiband.com](http://www.pemsa-rejiband.com)



Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

## Product data

|                                              |                    |                                       |                            |
|----------------------------------------------|--------------------|---------------------------------------|----------------------------|
| <b>ETIM 10</b>                               | EC001535           | <b>kg/u</b>                           | 2,831                      |
| <b>Huella de CO2. GWP A1-A3 (kg CO2 eq.)</b> | 9,144              | <b>u</b>                              | 1                          |
| <b>Protection System</b>                     | PG                 | <b>Material</b>                       | Steel with surface coating |
| <b>Finish</b>                                | PG3, Pregalvanised | <b>Impact Strength (J)</b>            | 20 J                       |
| <b>Resistance Class</b>                      | Class 3            | <b>Working temperature range (°C)</b> | -50 / 150 °C               |
| <b>Flange (mm)</b>                           | 120                | <b>Fire resistance</b>                | A1 No combustible          |
| <b>Width (mm)</b>                            | 150                |                                       |                            |
| <b>R (mm)</b>                                | 300                |                                       |                            |

## 🔒 Protection System

**CU** - Copper electroplated

**PG** - Pregalvanised

**EZ** - Electrogalvanised

**BC** - Electrogalvanised Bichromate

**BK8** - High Resistance Coating

**GC** - Hot Dip Galvanising

**INOX** - Stainless Steel

**PT** - Polyester Paint

**AL** - Aluminum

**LN** - Brass or Nickel-plated brass

## 🏠 Insulating materials

**PC+ABS** - Halogen Free Polycarbonate + ABS

**PVC** - Polyvinyl Chloride

**PP** - Halogen Free Polypropylene

**PA6** - Halogen Free Polyamide 6

**PA12** - Halogen Free Polyamide 12

**PU** - Polyurethane

**PE** - Polyethylene

**NBR** - NBR rubber

**PET** - Thermoplastic Polyester

**TPV** - Thermoplastic



[www.pemsa-rejiband.com](http://www.pemsa-rejiband.com)

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



## Product applications

