
Cable Tray Accessories 30/04/2024

Inside Riser Click (Ref: 70055215)









1/2







Description

Metal accessory for the creation of a 90° Inside Riser in the wiring installation of Pemsaband® and Inducanal® tray. Of 60 mm height, Width 150 mm, With INOX protection system, I304 finish. It enables a change of height in a vertical direction and avoids any damage in the routing of the cables. Quick connection assembly using the Click system without couplers. Made of steel in various sizes and Protection Systems.

Advantages

Side flanges have the same profile as the straight section of the trays thus forming a continual view of the installation.

It has pre-formed holes in the sides to allow for the connection of fittings and conduits for the exit of cables.

Available in all sizes and protection systems: PG, GC and stainless steel AISI304 and AISI316.

The PG protection system is supplied flat for later assembly and provides savings on transportation and storage by reducing its volume.

Assembly by means of the quick-connect click system without the need for couplers. Patented Universal System that has holes compatible with the connection to other sheet metal tray.

Applications

Suitable for the creation of an Inside Riser in the Pemsaband® One perforated and solid ranges for the Support, management and distribution of Electrical and/or telecommunications cables in public buildings, infrastructures and civil works, tertiary sector and industrial applications.

Solutions













Cable Tray Accessories 30/04/2024

Inside Riser Click (Ref: 70055215) 2/2

Product data			
Protection System	INOX	u	1
Finish	Stainless Steel AISI 304	Material	Stainless steel AISI 304
Resistance Class	Class 9C	Impact Strength (J)	20 J
Flange (mm)	60	IP	IP44
Width (mm)	150	Working temperature range (°C)	-50 / 150 °C
R stat. (mm)	100	Fire resistance	A1 No combustible
kg/u	0.516		

S Protection System

- CU Copper electroplated
- PG Pregalvanised
- EZ Electrogalvanised
- BC Electrogalvanised Bichromate
- **BK8** High Resistance Coating
- GC Hot Dip Galvanising
- INOX Stainless Steel
- PT Polyester Paint
- AL Aluminum
- LN Brass or Nickel-plated brass

M Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

- PVC Polyvinyl Chloride
- PP Halogen Free Polypropylene
- PA6 Halogen Free Polyamide 6
- PA12 Halogen Free Polyamide 12
- PU Polyurethane
- PE Polyethylene
- NBR NBR rubber
- PET Thermoplastic Polyester
- TPV Thermoplastic













