

PQ Outside Riser PQU AL Outside Riser



Description

Metal accessory for creating an outside riser in the wiring installation with the Pemsaband® PQU AL tray. It allows ascents and height changes to be made with great ease, avoiding damage to the cable routing. Assembly using bolts. Made from Aluminium alloy 1050H24.

Advantages

Available in 30, 50 and 60 mm height and 100, 200, 300, 400, and 600 mm wide.

Its conical tip allows more contact with the element to which it is screwed.

CEPSA product approval. Designed according to ESP-2208-5 specification.

Conforms to IEC 61537 and CE Conformity to Directive 2014/35/EU.

Made of Aluminum alloy 1050H24. Excellent corrosion resistance and mechanical properties.

Applications

Suitable for fixing Rejiband® trays to supports for cable management in electrical and telecommunications installations, industrial installations, infrastructure and civil works and the service sector.

Solutions



PQ Outside Riser PQU AL Outside Riser

Main technical characteristics

AL	30, 60	100, 200, 300, 400, 600	200	1	Aluminum	20 J	-50 / 150 °C	
A1 No combustible		ETIM 10 EC002400						

Product data

		Ref	kg/u
30	100	82002358	0,547
30	200	82002359	0,888
30	300	82002360	1,230
30	400	82002361	1,570
30	600	82002362	2,250
60	100	82002363	0,806
60	200	82002364	1,150
60	300	82002365	1,490
60	400	82002366	1,830
60	600	82002367	2,510

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic

