



### Description

Connector for mounting two M8 threaded rods in order to obtain the suitable length for the installation from the ceiling of the electrical installation, 30 mm long and an external diameter of 12 mm, with BC Protection System. M 8, M 8

### Advantages

BC protection system (standard EN-ISO 2081), gold colour, better corrosion resistance, suitable for indoor installations. Corrosion resistance class 5.

CE conformity to directive 2014/35 / EU.

It provides the necessary rigidity so that deformation does not occur.

Joining of sections of 500 mm and 1000 mm M8 rod.

### Applications

Used for the joining of M8 threaded rods as a support and ceiling mounting for Rejiband® and Pemsaband® trays in the management and distribution of electrical wiring and/or telecommunications.

### Solutions



Product data			
Protection System	EZ	u	50
Finish	EZ2, Electrogalvanised	Material	Steel with surface coating
Resistance Class	Class 2	Working temperature range (°C)	-50 / 150 °C
M/PG	M 8	Fire resistance	A1 No combustible
kg/u	0.019		

🔒 Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

🔒 Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic