



Description
Advantages
Applications
Solutions

90° bend Pemsaband Vulcan

Main technical characteristics

PG3, Pregalvanised, ZM High Resistance Alloy	12, 18, 25, 50	50, 75, 100, 150, 225, 300, 450, 600, 750, 900	1
Steel with surface coating	20 J	IP44	-50 / 150 °C
		A1 No combustible	ETIM 10

Product data

§	®	Class EC 61537	12	18	Ref	kg/u
PG	PG3, Pregalvanised	Class 3	12	50	82004712	0,162
PG	PG3, Pregalvanised	Class 3	12	75	82004713	0,230
PG	PG3, Pregalvanised	Class 3	12	100	82004714	0,306
PG	PG3, Pregalvanised	Class 3	12	150	82004715	0,456
PG	PG3, Pregalvanised	Class 3	12	225	82004716	0,754
PG	PG3, Pregalvanised	Class 3	18	300	82004717	1,710
PG	PG3, Pregalvanised	Class 3	25	50	82004718	0,221
PG	PG3, Pregalvanised	Class 3	25	75	82004719	0,298
PG	PG3, Pregalvanised	Class 3	25	100	82004720	0,372
PG	PG3, Pregalvanised	Class 3	25	150	82004721	0,531
PG	PG3, Pregalvanised	Class 3	25	225	82004722	0,837
PG	PG3, Pregalvanised	Class 3	25	300	82004723	1,803
PG	PG3, Pregalvanised	Class 3	25	450	82004724	3,169
PG	PG3, Pregalvanised	Class 3	25	600	82004725	4,861
PG	PG3, Pregalvanised	Class 3	50	50	82004726	0,319
PG	PG3, Pregalvanised	Class 3	50	75	82004727	0,399
PG	PG3, Pregalvanised	Class 3	50	100	82004728	0,479
PG	PG3, Pregalvanised	Class 3	50	150	82004729	0,652
PG	PG3, Pregalvanised	Class 3	50	225	82004730	1,475
PG	PG3, Pregalvanised	Class 3	50	300	82004731	2,043
PG	PG3, Pregalvanised	Class 3	50	450	82004732	3,469
PG	PG3, Pregalvanised	Class 3	50	600	82004733	5,220
PG	PG3, Pregalvanised	Class 3	50	750	82004734	12,117
PG	PG3, Pregalvanised	Class 3	50	900	82004735	16,232
PG	PG3, Pregalvanised	Class 3	25	750	82004736	11,416
PG	PG3, Pregalvanised	Class 3	25	900	82004737	15,435
AZ+	ZM High Resistance Alloy	Class 8	25	750	82004738	11,416
AZ+	ZM High Resistance Alloy	Class 8	25	900	82004739	15,435
AZ+	ZM High Resistance Alloy	Class 8	25	50	82004740	0,221
AZ+	ZM High Resistance Alloy	Class 8	25	75	82004741	0,298
AZ+	ZM High Resistance Alloy	Class 8	25	100	82004742	0,372
AZ+	ZM High Resistance Alloy	Class 8	25	150	82004743	0,531
AZ+	ZM High Resistance Alloy	Class 8	25	225	82004744	0,837
AZ+	ZM High Resistance Alloy	Class 8	25	300	82004745	1,803
AZ+	ZM High Resistance Alloy	Class 8	25	450	82004746	3,169



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



§	Ⓕ	EN 61537	Ⓜ	Ⓜ	Ref	kg/u
AZ+	ZM High Resistance Alloy	Class 8	25	600	82004747	4,861
AZ+	ZM High Resistance Alloy	Class 8	50	50	82004748	0,319
AZ+	ZM High Resistance Alloy	Class 8	50	75	82004749	0,399
AZ+	ZM High Resistance Alloy	Class 8	50	100	82004750	0,479
AZ+	ZM High Resistance Alloy	Class 8	50	150	82004751	0,652
AZ+	ZM High Resistance Alloy	Class 8	50	225	82004752	1,475
AZ+	ZM High Resistance Alloy	Class 8	50	300	82004753	2,043
AZ+	ZM High Resistance Alloy	Class 8	50	450	82004754	3,469
AZ+	ZM High Resistance Alloy	Class 8	50	600	82004755	5,220
AZ+	ZM High Resistance Alloy	Class 8	50	750	82004972	12,117
AZ+	ZM High Resistance Alloy	Class 8	50	900	82004973	16,232

§ Protection System

- CU** - Copper electroplated
- PG** - Pregalvanised
- EZ** - Electrogalvanised
- BC** - Electrogalvanised Bichromate
- BK8** - High Resistance Coating
- GC** - Hot Dip Galvanising
- INOX** - Stainless Steel
- PT** - Polyester Paint
- AL** - Aluminum
- LN** - Brass or Nickel-plated brass

Ⓜ Insulating materials

- PC+ABS** - Halogen Free Polycarbonate + ABS
- PVC** - Polyvinyl Chloride
- PP** - Halogen Free Polypropylene
- PA6** - Halogen Free Polyamide 6
- PA12** - Halogen Free Polyamide 12
- PU** - Polyurethane
- PE** - Polyethylene
- NBR** - NBR rubber
- PET** - Thermoplastic Polyester
- TPV** - Thermoplastic