



### Description

Spiral tape for the wrapping and protection of cables. Available in different sizes. Made of polyethylene, white RAL 9010 or black RAL 7021.

### Advantages

CE conformity to the 2014/35 directive and the IEC 61386 standard.

Available in two colours: White RAL 9010 and black RAL 9005.

Made of polyethylene.

No flame propagation.

### Applications

Suitable for the wrapping and management of cables in general applications.

### Solutions



Product data			
Colour		Black RAL 9005	
Cable diameter range		8 / 60	
kg/u			0.029
Ø d1 (mm)		5.4	
Material			Polyethylene
Ø d2 (mm)		8	
Working temperature range (°C)			-45 / 90 °C
Ø C (mm)		10	
Fire resistance			Flame retardant

Protection System	
CU	- Copper electroplated
PG	- Pregalvanised
EZ	- Electrogalvanised
BC	- Electrogalvanised Bichromate
BK8	- High Resistance Coating
GC	- Hot Dip Galvanising
INOX	- Stainless Steel
PT	- Polyester Paint
AL	- Aluminum
LN	- Brass or Nickel-plated brass

Insulating materials	
PC+ABS	- Halogen Free Polycarbonate + ABS
PVC	- Polyvinyl Chloride
PP	- Halogen Free Polypropylene
PA6	- Halogen Free Polyamide 6
PA12	- Halogen Free Polyamide 12
PU	- Polyurethane
PE	- Polyethylene
NBR	- NBR rubber
PET	- Thermoplastic Polyester
TPV	- Thermoplastic