
Assembly Accessories

Side Connector

25/04/2024













Description

Set of two metallic pieces, one for each side, with safety edge for the creation of tees and joints in installations of Megaband® ladder. Made of steel, with GC Protection System. Available in different sizes.

Advantages

Allows you to configure a side connection with different angles.

Facilitates the side exit of a cable.

Wide product range for all side heights of Megaband®ladder, 60, 85, 100 and 120 mm.

Applications

Suitable for cable management in electrical and telecommunications installations in public buildings, infrastructures and civil works, industrial facilities, tertiary sector. Designed to withstand very high loads.

Solutions













25/04/2024 Assembly Accessories

Side Connector

2/3

Main technical characteristics

(S) GC

Class 6

60, 100, 120

₩ 1

***** -50 / 150 °C

A1 No combustible

ETIM EC002935

Product data

	Res	kg/u
60	93930202	1.220
100	93930204	1.800
120	93930205	2.040

S Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

™ Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic













Assembly Accessories **Side Connector** 25/04/2024

3/3

Product applications

