



Description

Elasticated monofilament sheath, halogen-free, for cable management. Available in different diameters. Made of self-extinguishing polyamide 6, grey RAL 7035 and black RAL 9005.

Advantages

CE conformity to the 2014/35 directive and the IEC 61386 standard.

Available in colours: grey RAL 7035 and black RAL 9005.

Manufactured in polyamide 6. Self-extinguishing, halogen-free according to UNE/EN 60754-2 y UNE/EN 60754-1 and flame-retardant.

Halogen free.

Applications

Suitable for the protection and management of wiring for general and industrial applications.

Solutions



Product data			
Colour		Grey RAL 7031	
DN		NW 8	
Cable diameter range		7 / 11	
A (mm)		7	
B (mm)		11	
kg/u		0.006	
u		100	
Material		Poyamide 6	
Working temperature range (°C)		-25 / 150 °C	
Fire resistance		LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA	

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic