



## Description

Elasticated monofilament sheath, halogen-free, for cable management. Available in different diameters. Made of self-extinguishing polypropylene in grey colour RAL 7035.

## Advantages

CE conformity to the 2014/35 directive and the IEC 61386 standard.

Available in grey colour RAL 7035.

Made of self-extinguishing polypropylene.

Halogen free.

## Applications

Suitable for the protection and management of wiring for general and industrial applications.

## Solutions



[www.pemsa-rejiband.com](http://www.pemsa-rejiband.com)

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



Product data			
Colour		Grey RAL 7031	
DN		NW25	
Cable diameter range		24 / 36	
A (mm)		24	
B (mm)		36	
kg/u		0.018	
u		100	
Material		Polypropylene	
Working temperature range (°C)		-25 / 150 °C	
Fire resistance		LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA	

Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass

Insulating materials
PC+ABS - Halogen Free Polycarbonate + ABS
PVC - Polyvinyl Chloride
PP - Halogen Free Polypropylene
PA6 - Halogen Free Polyamide 6
PA12 - Halogen Free Polyamide 12
PU - Polyurethane
PE - Polyethylene
NBR - NBR rubber
PET - Thermoplastic Polyester
TPV - Thermoplastic