



Description

Lid fixing for use on the Pemsaband® PQU tray. Of 60 mm height, With INOX protection system, I304 finish. It provides more security to the system during wind or inclement weather. Made from AISI 304 stainless steel.

Advantages

CE certified in compliance with the low voltage directive 2014/35 / EU

Fixing element to give a greater closure to the Pemsaband PQU AL cable tray

Made of Aluminum alloy 1050H24. Excellent corrosion resistance and mechanical properties.

Allows greater protection of wiring in aggressive environments.

CEPSA product approval. Designed according to ESP-2208-5 specification.

Applications

Suitable for fixing Rejiband® trays to supports for cable management in electrical and telecommunications installations, industrial installations, infrastructure and civil works and the service sector.

Solutions



ETIM 10	EC001002
Huella de CO2. GWP A1-A3 (kg CO2 eq.)	
Protection System	INOX
Finish	Stainless Steel AISI 304
Resistance Class	Class 9C
Flange (mm)	60
kg/u	0,067

u	4
Material	Stainless steel AISI 304
Working temperature range (°C)	-50 / 150 °C
Fire resistance	A1 No combustible

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic



Product applications

