


20/04/2024 Accessories









Description

Flat ring of NBR elastomer in blue colour, metric and PG thread for use with external threaded fittings and cable glands to provide an IP67 protection index to the joint. Available in various sizes.

Advantages

Improves the seal of the fitting or cable gland on the box, reaching IP67.

Available in metric thread: M12, M16, M20, M25, M32, M40 M50 and M63 and PG thread: 7, 9, 11, 13.5, 16, 21, 29, 36 and 48.

CE conformity to the 2014/35 directive and the IEC 61386 standard.

Manufactured in NBR elastomer.

Applications

Suitable for use on an external thread to improve the tightness of the joint with the boxes. Can be used for any range of fittings, conduits or cable glands.

Solutions















20/04/2024 Accessories

Flat Ring

2/3

Main technical characteristics

CoLOUR Blue RAL 5024

***** -25 / 105

Flame retardant

EC000098

Product data

	Rer	kg/u	G i
PG 7	39092007	0.000	100
PG 9	39092009	0.001	100
PG11	39092011	0.001	100
PG13	39092013	0.001	50
PG16	39092016	0.001	50
PG21	39092021	0.001	50
PG29	39092029	0.001	30
PG36	39092036	0.001	10
PG48	39092048	0.002	10
M12	39092112	0.000	50
M16	39092116	0.000	50
M20	39092120	0.001	50
M25	39092125	0.001	50
M32	39092132	0.001	30
M40	39092140	0.002	10
M50	39092150	0.003	10
M63	39092163	0.002	10

S Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

⊗ Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6















3/3



20/04/2024 Accessories

Flat Ring

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic













