Kit Suspension Cable tray

Description

Cable suspension kit for Pemsaband® sheet trays and other items such as luminaires, air conditioning, signalling, etc. This Spiderband® suspension kit consists of asteel cable + block and a Y shape suspension for the sheet tray. It is available in cable lengths of 1 and 3 metres and Y suspensions of 300 and 460 mm. With a maximum load of 35 and 90 kg. Made of steel and with EZ Protection System.

Advantages

Optimised design for quick and easy use. Installation savings in both material and labour.

Flexible system with various support options in structures, beams, large spans, etc.

Suitable for the support of cable trays or other items with loads between 35 and 90 kg according to the reference.

CE conformity to directive 2014/35 / EU.

PG protection system (standard EN-ISO 2081), silver colour, suitable for indoor installations. Corrosion resistance class 3.

Applications

Suitable for support by cable suspension of Pemsaband® sheet trays, as well as other items (luminaires, air conditioning, signage, etc.). Recommended for indoor installations.

Solutions

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

Kit Suspension Cable tray

Main technical characteristics

EZ	10	Steel with surface coating	-50 / 150 °C	Flame retardant	ETIM EC001003

Product data

	L(mm)	REF	kg/u	CTA (kg)
1	300	62308231	0.047	35
3	300	62308233	0.084	35
1	460	62308241	0.047	35
3	460	62308243	0.084	35
1	300	62308631	0.099	90
3	300	62308633	0.175	90
1	460	62308641	0.099	90
3	460	62308643	0.175	90

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."