



Description

Loop + Block Suspension for Rejiband® wire mesh trays, Pemsaband® sheet trays and other items such as luminaires, pipes, air conditioning, signalling, etc. Length of 3 metres. The Spiderband® suspension system consists of a cable with a loop on one end and the self-locking block on the other. Available in lengths of 1, 3 and 5 metres, with maximum loads of 10, 45 and 90 kg. Made of steel and with EZ Protection System.

Advantages

PG protection system (standard EN-ISO 2081), silver colour, suitable for indoor installations. Corrosion resistance class 3.

CE conformity to directive 2014/35 / EU.

Optimised design for quick and easy use. Installation savings in both material and labour.

Quick and direct fixing of Rejiband® wire mesh trays and Pemsaband® trays, together with other carabiner and tray suspension items.

Flexible system with various support options in structures, beams, large spans, etc.

Applications

Suitable for support by wire suspension of Rejiband® wire mesh and Pemsaband® sheet trays, as well as other items (luminaires, pipes, air conditioning, signage, etc.). Recommended for indoor installations.

Solutions



Product data			
Protection System	EZ	u	10
Finish	EZ2, Electrogalvanised	Material	Steel with surface coating
Length (m)	3	SWL (kg)	90
kg/u	0.171	Working temperature range (°C)	-50 / 150 °C

Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass

Insulating materials
PC+ABS - Halogen Free Polycarbonate + ABS
PVC - Polyvinyl Chloride
PP - Halogen Free Polypropylene
PA6 - Halogen Free Polyamide 6
PA12 - Halogen Free Polyamide 12
PU - Polyurethane
PE - Polyethylene
NBR - NBR rubber
PET - Thermoplastic Polyester
TPV - Thermoplastic