



Description

Plug to make a fixation and a tightness of a cable with terminal, diameter, NW 5 mm, for internal thread gland Placement PG13.

Advantages

Applications

Solutions



Product data

Colour	Black RAL 9005	u	50
DN	NW 5	Material	NBR
M/PG	PG13	IP	IP65
Ø d2 (mm)	16	Working temperature range (°C)	-40 / 100 °C
Holes	1	Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA
kg/u	0.002		

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

