

Description

Megaband® Marine ladder for installation in ships, naval and offshore environments. The Megaband Marine Tray It is configured with 4mm thick side rails and Z-format rungs with multi-perforations. Made from steel, available in various protection systems.

Advantages

Flange height 150 mm and available in widths of 200, 400, 450, 500 and 600 mm with a wide range of accessories.

The side rail of the Megaband® Marine in GC Protection system has triangular perforations that allow cutting and bending these side rails to perform inside and outside risers. Additionally, they also allow us to manipulate the side rail transversely to create bends of different angles to 90° on the same plane, making changes of direction to overcome obstacles in the layout of the installation.

CE certified in compliance with the low voltage directive 2014/35 / EU

SAFECu Protection system, copper-plated treatment, which confers hygienic properties by eliminating bacteria, viruses and fungi

Applications










Solutions



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

Main technical characteristics

 40	 100, 200, 300, 400, 500, 600	 2	 2	 20 J	 4	 1	 -50 / 150 °C
ETIM							
 A1 No combustible							

Product data

Ⓢ	Class BC 61537	Ⓜ	Ref	kg/u	Ⓜ
GC	Class 8	100	82003116	2.730	Steel with surface coating
GC	Class 8	200	82003117	3.200	Steel with surface coating
GC	Class 8	300	82003118	3.670	Steel with surface coating
GC	Class 8	400	82003119	4.140	Steel with surface coating
GC	Class 8	500	82003120	4.610	Steel with surface coating
GC	Class 8	600	82003121	5.080	Steel with surface coating
INOX	Class 9D	100	82003122	2.710	Acero inoxidable AISI 316L
INOX	Class 9D	200	82003123	3.130	Acero inoxidable AISI 316L
INOX	Class 9D	300	82003124	3.560	Acero inoxidable AISI 316L
INOX	Class 9D	400	82003125	3.980	Acero inoxidable AISI 316L
INOX	Class 9D	500	82003126	4.400	Acero inoxidable AISI 316L
INOX	Class 9D	600	82003127	4.830	Acero inoxidable AISI 316L

Ⓢ Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Ⓜ Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester

TPV - Thermoplastic



Product applications

