




Description

Metal cover used as an end closure for the Megaband® ladder system. Of 120 mm height, Width 200 mm, With GC protection system, HDG finish. Quick connection assembly using the click system, without joints. Made of steel, in various sizes and Protection Systems.

Advantages

Safer professional finish.

Available in various sizes.

Its unique design allows the closure and protection of Megaband ladder.

Applications

It is used as a closure on the end of the Megaband® ladder system for the protection of the installation. Applicable in the management of cables in electrical and telecommunications installations in public buildings, infrastructures and civil works, industrial installations, tertiary sector.

Solutions



Product data			
ETIM 10		EC001574	
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		1,003	
Protection System		GC	
Finish		HDG, Hot Dip Galvanised	
Resistance Class		Class 5	
Flange (mm)		120	
Width (mm)		200	
kg/u		0,387	
u		1	
Material		Steel with surface coating	
IP		IP44	
Working temperature range (°C)		-50 / 150 °C	
Fire resistance		A1 No combustible	

Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass

Insulating materials
PC+ABS - Halogen Free Polycarbonate + ABS
PVC - Polyvinyl Chloride
PP - Halogen Free Polypropylene
PA6 - Halogen Free Polyamide 6
PA12 - Halogen Free Polyamide 12
PU - Polyurethane
PE - Polyethylene
NBR - NBR rubber
PET - Thermoplastic Polyester
TPV - Thermoplastic

Product applications



