



Description

Reinforced ladder for large elevated loads in heavy industry. Of 120 mm height, Width 600 mm. The Megaband® REP ladder is made up of alternating welded steel rungs 250mm high and a safety edge to protect and strengthen the ladder. Made from steel with GC Protection system.

Advantages

Wide variety of sizes and accessories to adapt to the demands of each electrical installation.

In accordance with the IEC 61537 and CE standard with respect to directive 2014/35 / EU.

Specially designed for the petrochemical sector, with REPSOL approvals, ED-P-11-02

4mm side rails and 3mm rungs thickness.

GC Protection System. Hot dip Galvanised with 85 microns of thickness. Class 8 according to IEC 61537.

Applications

This ladder is especially suitable for electrical installations to support large loads in industrial, petrochemical, oil & gas, power plant, mining and cement plants.

Solutions



Product data

ETIM 10	EC000854	u	6
Huella de CO2. GWP A1-A3 (kg CO2 eq.)	222,222	Material	Steel with surface coating
Protection System	GC	Impact Strength (J)	20 J
Finish	HDG, Hot Dip Galvanised	Thickness (mm)	4
Resistance Class	Class 8	Section (mm2)	57600
Flange (mm)	120	Working temperature range (°C)	-50 / 150 °C
Width (mm)	600	Fire resistance	A1 No combustible
Length (m)	6		
kg/u	14,300		

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic

Product applications

□ □



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

