



### Description

Cable suspension system for for Rejiband® wire mesh tray or other items. This type of Spiderband® suspension is fixed to the rod of the tray by means of a carabiner to each side of the tray, without the need for screws. Maximum admissible load of 50 kg. Made of steel, with EZ Protection System and available in lengths of 300 and 460 mm.

### Advantages

Optimised design for quick and easy use. Installation savings in both material and labour.

It has a loop on the end for the connection of the steel cable.

Suitable for the support of wire mesh trays and other items with loads not exceeding 50 kg.

CE conformity to directive 2014/35 / EU.

PG protection system (standard EN-ISO 2081), silver colour, suitable for indoor installations. Corrosion resistance class 3.

### Applications

Suitable for support by cable suspension of Rejiband® wire mesh trays, as well as other items (luminaires, air conditioning, signaling, etc.). Recommended for indoor installations.

### Solutions



Main technical characteristics

Ⓢ EZ	🔗 10	Ⓜ Steel with surface coating	CTA 50	🔥 -50 / 150 °C	🔥 Flame retardant	ETIM EC001003
------	------	------------------------------	--------	----------------	-------------------	---------------

Product data

L <sub>mm</sub>	Ref	kg/u
300	62305430	0.049
460	62305440	0.055

Ⓢ Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Ⓜ Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

