

SAFECu SPLUS Omega Pendant

1/2



Description

Omega profile pendulum for ceiling mounting Rejiband® SAFECu trays. Ceiling fixing system that allows different structures to be configured individually or with the help of the omega SPLUS support. Available in lengths of 400, 500 and 600mm. Made from steel with CU protection system.

Advantages

Suitable as ceiling fixing of cable trays for antimicrobial and COVID-free cable management systems

Permanent 24/7 protection without any additional maintenance

Available in lengths 400 to 600 mm.

CE conformity in accordance to the low voltage directive 2014 /35 /UE and the international product standard IEC 61537

SAFECu Protection system, copper-plated treatment, which confers hygienic properties by eliminating bacteria, viruses and fungi

Applications

Adecuado para soportar cargas medias en bandejas portacables Rejiband® SAFECu a techo para instalaciones eléctricas y/o de telecomunicaciones en: Unidades UCI y quirófanos, habitaciones y salas de espera de centros sanitarios y hospitales, nuevos desarrollos de hospitales y hospitales provisionales, centros geriátricos y asistenciales colegios, universidades y centros de enseñanza obras civiles, túneles, parkings, edificios públicos, centros comerciales, centros de proceso de datos, grandes infraestructuras, aeropuertos, líneas de metro, tren, sector terciario y aplicaciones industriales.

Solutions



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



Main technical characteristics

 CU	 Class 1	 300, 400, 500, 600	 5	 Steel with surface coating	 -50 / 150 °C	 A1 No combustible
ETIM						

Product data

	Ref	kg/u	JE _{reg}	MF1 _{reg}	MF2 _{reg}
300	82003273	0.552	200	9	7
400	82003274	0.670	200	7	6
500	82003275	0.814	300	8	7
600	82003276	0.937	350	10	9

 Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

 Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic

