


Side Joint Plate (Ref: 64080041)

1/4



Description

Metal side joining piece in various Protection Systems for the assembly of different sections of Rejiband trays. With BK8 protection system, BK8-ZNI finish. Excellent adjustment with maximum load values, ensuring mechanical strength of the joint and electrical continuity, according to IEC61537 standard. For the installation of trays, the connecting plate is installed on the side of the tray and connected by means of the Rejiband Part Clamp. It is an accessory for the assembly of Rejiband trays, made of steel and available in different Protection Systems.

Advantages

Suitable for trays 60 to 600 mm wide.

Available in various protection systems: EZ, BC, GC, high resistance BK C8 and passivated stainless steel AISI 316.

Reinforces the joint between different sections of the tray with the use of the Rejiband fixing.

Side connection for Rejiband trays.

Applications

Suitable for the joining of straight sections of Rejiband tray in all types of wall or ceiling mounted electrical installations.

Solutions



www.pemsa-rejiband.com



Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

Product data			
ETIM 10		EC002413	
Huella de CO2. GWP A1-A3 (kg CO2 eq.)			
Protection System		BK8	
Finish		Zinc Nickel black	
Resistance Class		Class 8	
kg/u		0,051	
u		50	
Material		Steel with surface coating	
Working temperature range (°C)		-50 / 150 °C	
Fire resistance		A1 No combustible	

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

Product applications

