



Description

Plug to make a fixation and a tightness of 2 Diameter cables, NW 6 mm, for internal thread gland Placement PG13.

Advantages

Applications

Solutions



Product data			
Colour	Black RAL 9005	u	50
DN	NW 6	Material	NBR
M/PG	PG13	IP	IP65
Ø d2 (mm)	16	Working temperature range (°C)	-40 / 100 °C
Holes	2	Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA
kg/u	0.001		

Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass

Insulating materials
PC+ABS - Halogen Free Polycarbonate + ABS
PVC - Polyvinyl Chloride
PP - Halogen Free Polypropylene
PA6 - Halogen Free Polyamide 6
PA12 - Halogen Free Polyamide 12
PU - Polyurethane
PE - Polyethylene
NBR - NBR rubber
PET - Thermoplastic Polyester
TPV - Thermoplastic