



Description

Plug to make a fixation and a tightness of 16 Diameter cables, NW 3 mm, for internal thread gland Placement PG29.

Advantages

Applications

Solutions



## Product data

|                  |                |                                       |  |
|------------------|----------------|---------------------------------------|--|
| <b>Colour</b>    | Black RAL 9005 | <b>u</b>                              | 5  |
| <b>DN</b>        | NW 3           | <b>Material</b>                       | NBR  |
| <b>M/PG</b>      | PG29           | <b>IP</b>                             | IP65   |
| <b>Ø d2 (mm)</b> | 30             | <b>Working temperature range (°C)</b> | -40 / 100 °C                                 |
| <b>Holes</b>     | 16             | <b>Fire resistance</b>                | LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA |
| <b>kg/u</b>      | 0.008          |                                       |  |

## Protection System

**CU** - Copper electroplated

**PG** - Pregalvanised

**EZ** - Electrogalvanised

**BC** - Electrogalvanised Bichromate

**BK8** - High Resistance Coating

**GC** - Hot Dip Galvanising

**INOX** - Stainless Steel

**PT** - Polyester Paint

**AL** - Aluminum

**LN** - Brass or Nickel-plated brass

## Insulating materials

**PC+ABS** - Halogen Free Polycarbonate + ABS

**PVC** - Polyvinyl Chloride

**PP** - Halogen Free Polypropylene

**PA6** - Halogen Free Polyamide 6

**PA12** - Halogen Free Polyamide 12

**PU** - Polyurethane

**PE** - Polyethylene

**NBR** - NBR rubber

**PET** - Thermoplastic Polyester

**TPV** - Thermoplastic

