Pemsaband PQU AL Joints

17/11/2026



# Serrates Hexagon Flange Nut M6 ( Ref: 64060059 )



## Description

M6 metal nut with serrated flange to be used together with a bolt for the fixing of accessories, brackets or joining straight sections of Pemsaband® trays. M 6, M 6, With INOX protection system, I316L finish. Suitable for Pemsaband® trays of 35, 60 and 85 mm in height.

## Advantages

CE conformity to directive 2014/35 / EU.

Available in different protection systems: EZ, BK8, GC, and stainless steel AISI 316.

The serrated edge reinforces the tightening of the nut on the bolt.

Very versatile piece.

## Applications

Suitable for the fixing together, along with the C/Din screw, of straight sections, accessories, bends, tees and supports for installations of Pemsaband® One perforated and solid, Pemsaband® PQU and Pemsaband® PQW metal trays in the management and distribution of cables for Petrochemical, Oil & Gas, Offshore, Civil works and Infrastructure installations as well as for tunnels and installation galleries.

## Solutions



Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

# Serrates Hexagon Flange Nut M6 ( Ref: 64060059 )

## Product data

| | | | |
|---|---|---|---|
| **ETIM 10** | EC003863 | **u** | 50 |
| **Huella de CO2. GWP A1-A3 (kg CO2 eq.)** | | **Material** | Acero inoxidable AISI 316L |
| **Protection System** | INOX | **Working temperature range (°C)** | -50 / 150 ºC |
| **Finish** | Stainless Steel AISI 316L | **Fire resistance** | A1 No combustible |
| **Resistance Class** | Class 9D | | |
| **M/PG** | M 6 | | |
| **kg/u** | 0,004 | | |

## Ⓢ Protection System

**CU** - Copper electroplated

**PG** - Pregalvanised

**EZ** - Electrogalvanised

**BC** - Electrogalvanised Bichromate

**BK8** - High Resistance Coating

**GC** - Hot Dip Galvanising

**INOX** - Stainless Steel

**PT** - Polyester Paint

**AL** - Aluminum

**LN** - Brass or Nickel-plated brass

## Ⓜ Insulating materials

**PC+ABS** - Halogen Free Polycarbonate + ABS

**PVC** - Polyvinyl Chloride

**PP** - Halogen Free Polypropylene

**PA6** - Halogen Free Polyamide 6

**PA12** - Halogen Free Polyamide 12

**PU** - Polyurethane

**PE** - Polyethylene

**NBR** - NBR rubber

**PET** - Thermoplastic Polyester

**TPV** - Thermoplastic



Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."