
Serrated Hexagon Flange Nut (Ref: 64030059)





Description

M6 metal nut with serrated flange to be used together with a bolt for the fixing of accessories, brackets or joining straight sections of Pemsaband® trays. M 6, M 6, With GC protection system, ZNI finish. Suitable for Pemsaband® trays of 35, 60 and 85 mm in height.

Advantages

CE conformity to directive 2014/35 / EU.

Available in different protection systems: EZ, BK8, GC, and stainless steel AISI 316.

The serrated edge reinforces the tightening of the nut on the bolt.

Very versatile piece.

Applications

Suitable for the fixing together, along with the C/Din screw, of straight sections, accessories, bends, tees and supports for installations of Pemsaband® One perforated and solid, Pemsaband® PQU and Pemsaband® PQW metal trays in the management and distribution of cables for Petrochemical, Oil & Gas, Offshore, Civil works and Infrastructure installations as well as for tunnels and installation galleries.

Solutions

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

Serrated Hexagon Flange Nut (Ref: 64030059)

Product data

ETIM 10	EC003863	**u**	50
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		**Material**	Steel with surface coating
Protection System	GC	**Working temperature range (°C)**	-50 / 150 °C
Finish	Zinc Nickel	**Fire resistance**	A1 No combustible
Resistance Class	Class 8		
M/PG	M 6		
kg/u	0,004		

Ⓢ Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Ⓜ Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."