



### Description

Metal metric/PG thread adaptor for fittings and cable glands. Available in different sizes. Made of nickel-plated brass.

### Advantages

CE conformity to the 2014/35 directive and the IEC 61386 standard.

Made of nickel-plated brass.

Protection Index EN 60529: IP54 / IP68 (with O-ring).

### Applications

Suitable for adapting metric threads to PG and vice versa in cable glands and conduit fittings for the protection and management of wiring in general and industrial applications.

### Solutions



## Product data

<b>Protection System</b>	LTN	<b>L (mm)</b>	21
<b>Finish</b>	Nickel-plated brass	<b>kg/u</b>	0.040
<b>M/PG</b>	PG16	<b>u</b>	50
<b>G (mm)</b>	6.5	<b>Material</b>	Nickel-plated brass
<b>M/PG 2</b>	M25	<b>Working temperature range (°C)</b>	-45 / 150 °C
<b>Ø d2 (mm)</b>	27	<b>Fire resistance</b>	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA

## Protection System

- CU** - Copper electroplated
- PG** - Pregalvanised
- EZ** - Electrogalvanised
- BC** - Electrogalvanised Bichromate
- BK8** - High Resistance Coating
- GC** - Hot Dip Galvanising
- INOX** - Stainless Steel
- PT** - Polyester Paint
- AL** - Aluminum
- LN** - Brass or Nickel-plated brass

## Insulating materials

- PC+ABS** - Halogen Free Polycarbonate + ABS
- PVC** - Polyvinyl Chloride
- PP** - Halogen Free Polypropylene
- PA6** - Halogen Free Polyamide 6
- PA12** - Halogen Free Polyamide 12
- PU** - Polyurethane
- PE** - Polyethylene
- NBR** - NBR rubber
- PET** - Thermoplastic Polyester
- TPV** - Thermoplastic

