




Description

Cable gland with NBR soft rubber seal and IP68 protection rating (10 bar) according to EN 60529. Available in metric thread from M12 to M63 and PG7 to PG48 thread for various cable diameters. Made of self-extinguishing polyamide 6 in grey RAL 7035 and black RAL 9005. Industrial and special applications.

Advantages

Made of self-extinguishing Polyamide 6. V0 fire resistance according to UL 94. Halogen free. Resistant to UV radiation, UL_f1 classification.

Protection index EN 60529: IP68 with 10 bars of pressure for immersion in water.

Improved diaphragm closure system with NBR inner seal.

Working temperature: -40°C to + 100°C.

UL Classified Certification. Certification CSA, GL, VDE, EAC, NF. CE conformance with the 2014/35 directive and the IEC 62444 standard.

Applications

Its use is recommended in the manufacture of OEM equipment and outdoor, industrial and marine applications.

Solutions



RAILWAY APPLICATIONS



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



Main technical characteristics

 Colour		Grey RAL 7035						PG 7, PG 9, PG11, PG13, PG16, PG21, PG29, PG36, M12, M16, M20, M25, M32, M40, M50, M63												NBR,POLIAMIDA 6			
		IP68				-25 / 90 °C				LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA										ETIM 10		EC000441	

Product data

		Ø	Ø	L _{mm}	Ø	Ref	kg/u	
PG 7	8	3 / 6.5	9	29	15	22010007	0,004	50
PG 9	8	4 / 8	11	30	19	22010009	0,006	50
PG11	8	5 / 10	11	33	22	22010011	0,009	50
PG13	9	6 / 12	16	36	24	22010013	0,011	50
PG16	10	10 / 14	18	38	27	22010016	0,015	50
PG21	11	13 / 18	22	42	33	22010021	0,023	50
PG29	11	18 / 25	30	49	42	22010029	0,041	25
PG36	13	22 / 32	39	61	53	22010036	0,070	10
M12	8	3 / 6.5	9	29	15	22011120	0,004	50
M16	8	4 / 8	11	30	19	22011160	0,006	50
M16	8	5 / 10	14	33	22	22011161	0,009	50
M20	9	6 / 12	16	36	24	22011200	0,011	50
M20	9	10 / 14	18	37	27	22011201	0,015	50
M25	11	13 / 18	22	42	33	22011250	0,023	50
M32	11	18 / 25	30	50	42	22011320	0,041	25
M40	13	22 / 32	39	61	53	22011400	0,070	10
M50	13	32 / 38	45	62	60	22011500	0,091	5
M63	14	37 / 44	51	63	65	22011630	0,095	5

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene

Industrial HSK Cable gland
HSK-K Cablegland

17/09/2026
3/3

- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic

